

DIGITALLY PRINTABLE WALLCOVERING

Fabric Wallpaper

Vinyl wallcovering with non-woven backing · 350 g/m² · linen texture

A digitally printable linen textured contract-quality vinyl wallcovering with a non-woven backing. The linen texture adds a touch of refined luxury. This product is highly durable, fire retardant, colourfast, scrubbable, scratch and impact resistant, making it the perfect choice for hospitality venues and commercial spaces.

● PRODUCT CHARACTERISTICS

PROPERTIES	TEST METHOD	UNIT	VALUE	UNIT	VALUE
Total weight	ISO 536	g/m ²	350 ± 20	oz. l/y	± 15
Vinyl weight	ISO 536	g/m ²	300 ± 10	oz. l/y	± 13
Backing weight	ISO 536	g/m ²	50 ± 10	oz. l/y	± 2
Thickness	ISO 534	µm	360 ± 15	—	—
Opacity	ISO 2471	%	98	—	—

● PRODUCT FEATURES

| PRINT TECHNOLOGY

Eco-Solvent, Latex, UVgel, UV-curable.

| COLOURFASTNESS (PRIOR TO PRINTING)

7 out of 8, in accordance with ISO 105 B02
(1 = very poor, 8 = excellent).

| WASHABILITY

Scrubbable, in accordance with EN259-2 / EN12956.

Resistant to: Soap, Detergents, Alcohol, Ammonia, Alkali, Diluted Acids.

Non-resistant to: Solvents like Esters, Ketones, Aromatic hydrocarbons.

| FIRE RETARDANCY

Reaction-to-fire: B - s1, d0 in accordance with EN13501-1:2018.
Class "A" in accordance with ASTM E84-18a.

| SUSTAINABILITY

- Environmental Product Declaration available
- Low VOC - Class A+ according to French regulation on VOC emissions
- REACH compliant
- CE-marking in accordance with EN15102:2019

| SHELF-LIFE AND STORAGE CONDITIONS

The shelf life of this media is 2 years under normal conditions (10°C – 35°C at a relative humidity 30% - 75%). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place in its original packaging.

| OPERATING CONDITIONS

Maintain a guaranteed humidity level of 30% to 60%, preferably between 40% and 50% while printing and finishing, to ensure overall runnability reliability and prevent static electricity.

| APPLICATION

Paste-the-wall application, in accordance with instructions.

| SERVICE LIFE

Given the wallcovering is professionally installed, the reference service life is 10 years according to the German Sustainable Building Assessment System (BNB).

Important: before using the media the user must examine the suitability of the media for each application. We shall not assume liability for non-performance of the media. Specifications are subject to change without notice.