

DIGITALLY PRINTABLE WALLCOVERING

Canvas Wallpaper

Embossed vinyl on non-woven backing · 380 g/m² · white

A semi-finished wallcovering for plotter printing, consisting of a PVC coating applied on one side of a non-woven backing and subsequently embossed. The material is anisotropy, side different.

● PRODUCT CHARACTERISTICS

ESSENTIAL CHARACTERISTICS	VALUE
Weight	380 gr/m ² (±5%)
Standard color	White
Thickness	min. 0.31 mm — max. 0.35 mm
Roll specifications	106 cm x 60 m

● PRODUCT FEATURES

DETAILS OF ALL COMPONENTS

Backing: non-woven fabric 90 gr/m² (56% cellulose, 19% synthetic fibers, 22% Strich, 1% additives, 3% water).

PVC: 290 gr/m² (100% P.v.c. coating on one side).

PROCESSING PHASES

Coating, printing, embossing.

REACTION TO FIRE

Euro class B-s2, d0 in accordance with EN15102:2007+A1:2011.

IMO MED/3.18D.

USCG Category: 164.112 (module B) and (module D).

FLAME RETARDANT TREATMENT

Chemical retardants.

GENERAL INFORMATION

Semi-finished wallcovering for plotter printing. The material is anisotropy, side different.

APPLICATION

Printing base wall covering for plotter technology (latex, eco-solvent, solvent, UV systems).

END USE

Glued on incombustible support.

RECOMMENDED TYPE OF ADHESIVE

Adhesive for non-woven fabric supports.

STORAGE TEMPERATURE

Ideal storage between 20 °C and 30 °C.

Important: before using the media the user must examine the suitability of the media for each application. We shall not assume liability for non-performance of the media. Specifications are subject to change without notice.